APPLICATION FOR PERMISSION TO CHANGE POINT OF DIVERSION, MANNER OF USE AND PLACE OF USE OF THE PUBLIC WATERS OF THE STATE OF NEVADA HERETOFORE APPROPRIATED

NEVADA HERETOFORE APPROPRIATED
Date of filing in State Engineer's Office JAN 20 2000
Returned to applicant for correction
Corrected application filed
Map filed FEB 01 2000 under 65885-T
******* The applicant Getchell Gold Corporation, hereby makes application for permission to change the Point of diversion and place of use of all of water heretofore appropriated under Permit 62839 (Dewatering Well DW-4) (Replaces Temporary Application 65897T)

1. The source of water is underground
2. The amount of water to be changed 3 CFS; 706 MGA (full amount of Permit No. 62839)
3. The water to be used for mining, milling and dewatering
4. The water heretofore permitted for mining, milling, and dewatering
5. The water is to be diverted at the following point within SE¼ NE¼ section 33, T39N, R42E, MDM at a point from which the SW corner of said section 33 bears S 51° 07' 58" W, 5902.90 feet distant, from a pumping station in the Turquoise Ridge Vent Shaft.
6. The existing permitted point of diversion is located within SE½ NE½ section 33, T39N, R42E, MDM at a point from which the SW corner of said section 33 bears S 51° 00' 59" W., 6047.92 feet, from a well known as DW-4.
7. Proposed place of use within sections 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 25, 26, 27, 28, 29, 32, 33, 34, 35, and 36 in T39N, R42E, MDM; and sections 1, 2, 3, 4, 9, 10, 11, 12, 13, 14, 15, and 22 in T38N, R42E, MDM.
8. Existing place of use within sections 21, 22, 23, 26, 27, 28, 29, 32, 33 and 34 in T39N, R42E, MDM and sections 3, 4, 9, and 10 in T38N, R42E, MDM.
9. Use will be from January 1 to December 31 of each year.
10. Use was permitted from January 1 to December 31 of each year.
11. Description of proposed works See attached.
12. Estimated cost of works \$0; the works are existing.
13. Estimated time required to construct works 0 years ; the works are existing.
14. Estimated time required to complete the application of water to beneficial use 5 years
15. Remarks: This water to be pumped from the Turquoise Ridge Vent Shaft. The pumpage will serve to dewater the Turquoise Ridge underground workings. The water will be used for miscellaneous mining purposes including mining, milling, dust control, and drilling. Unused water will be treated and reinfiltrated to the ground water basin. s/Michael S. Smith By MICHAEL S. SMITH, AGENT
SAGE ENGINEERING
Compared my/ gkl hf/cmf 885 Lyman Ave., Reno, NV 89509

Protested_

APPROVAL OF STATE ENGINEER

This is to certify that I have examined the foregoing application, and do hereby grant the same, subject to the following limitations and conditions:

hereby grant the same, subject to the following limitations and conditions:

This permit to change the point of diversion and place of use of the waters of an underground source as heretofore granted under Permit 62839 is issued subject to the terms and conditions imposed in said Permit 62839 and with the understanding that no other rights on the source will be affected by the change proposed herein. A totalizing meter must be installed and maintained in the discharge pipeline near the point of diversion and accurate measurements must be kept of water placed to beneficial use. The totalizing meter must be installed before any use of the water begins or before the proof of completion of work is filed. This source is located within an area designated by the State Engineer pursuant to NRS 534.030.

This permit is issued under the preferred use provisions of NRS Chapter 534. The manner of use of water under this permit is by nature of its activity a temporary use and any application to change the manner of use granted under this permit will be subject to additional determination and evaluation with respect to the permanent effects on existing rights and the resource within the ground water basin.

This permit will allow the permittee to dewater the pit area and underground mining operations. It is understood that any water pumped as a result of this dewatering operation will be used first by the permittee for surface and underground mining, milling, leaching, drilling, road watering and other related mining uses hereinafter referred to as mining and milling uses within the described place of use of this permit.

The State Engineer retains the right to regulate pumping from the dewatering project and/or any other groundwater withdrawals herein authorized to protect the public interest and existing rights. Any water produced from this dewatering operation and not used for mining and milling purposes must be injected or infiltrated back to the Kelly Creek Groundwater Basin. Any injection or infiltration of water must have the necessary permits issued by the Nevada Division of Environmental Protection.

This permit does not extend the permittee the right of ingress and egress on public, private, or corporate land.

The issuance of this permit does not waive the requirements

The issuance of this permit does not waive the requirements that the permit holder obtain other permits from State, Federal and local agencies and is specifically issued contingent upon approval by the Nevada Division of Environmental Protection relating to the dewatering project.

relating to the dewatering project.

The total combined duty of water under Permits 28758, Certificate 13803; 45731, Certificate 13806; 45732, Certificate 13807; 49815, Certificate 13809; 58406; 58408; 61546; 61602; 61686; 61688; 63109, and 65900 through 65914, inclusive, shall not exceed 1,034.0 million gallons annually.

The total combined diversion rate under the above referenced permits and any subsequent changes to these permits shall not exceed 15.6 cubic feet per second (7,000 gallons per minute).

exceed 15.6 cubic feet per second (7,000 gallons per minute).

Monthly records will be kept and submitted quarterly for the following: (a) the volume of water pumped from each well, (b) the volume of water consumptively used for mining and milling uses projectwide, (c) the amount of water discharged to infiltration or injection, and the water level (static or pumping) of each permitted well and monitoring wells HL-1, DM-3, MW-16, MW-17, and MW-18. These records will be submitted within 15 days after the end of each quarter. A method that estimates the amount of evaporative losses will be considered as a part of the combined duty for consumptive purposes.

duty for consumptive purposes.

All flow measurements taken at those locations described in Covenant 2.3 (Flow Measurement) of the Water Resources Agreement between FirstMiss Gold, Inc. and LaVar Murdock, dba Adams Peak Properties, dated February 27, 1996, shall be reported in the above quarterly report.

All of the above stated conditions are issued subject to having no adverse impacts on existing rights.

(CONTINUED ON PAGE 3)

The amount of water to be appropriated shall be limited to the amount which can be applied to beneficial use, and not to exceed 3.0 cubic feet per second, but not to exceed 706.0 million gallons annually.

Work must be prosecuted with reasonable diligence and be completed on or before:

February 28, 2002

Proof of completion of work shall be filed before:

March 30, 2002

Water must be placed to beneficial use on or before:

February 28, 2003

Proof of the application of water to beneficial use shall be filed on or before: March 30, 2003

Map in support of proof of beneficial use shall be filed on or before: N/A

IN TESTIMONY WHEREOF, I, HUGH RICCI, P.E.,

State Engineer of Nevada, have hereunto set

my hand and the seal of my office,

this 9th day of, November A.D. 2000

State Engineer

Completion of work filed MAR 0 7 2002

Proof of beneficial use filed

Cultural map filed N/A

Certificate No. Issued

Turquoise Ridge Ventilation Shaft

Description of proposed works: The Turquoise Ridge Ventilation Shaft is an existing vertical shaft that provides ventilation air and a utility conduit for the Turquoise Ridge Underground Mine. Mine drainage water is gathered in a sump at the bottom of the mine, 1800 feet below the surface, and pumped, using Warman centrifugal pumps and an 8-inch discharge pipe, to the surface where it is commingled with other waters in the mine water system. A flow meter is located on the 8-inch discharge pipe at an underground working level 400 feet below the surface.

To accompany Getchell Gold Corporation's APPLICATION FOR PERMISSION TO CHANGE POINT OF DIVERSION, MANNER OF USE AND PLACE OF USE OF THE PUBLIC WATERS OF THE STATE OF NEVADA HERETOFORE APPROPRIATED for the following parent application numbers:

C:\PROJECT\94PROJEC\94007\CHPOD\PUMPDESP.WPD